



Decommissioning in Practice

Tony Owen, Subsea and Pipelines Decommissioning Delivery Manager

AOG | February 2017



Disclaimer and important notice



This presentation contains forward looking statements that are subject to risk factors associated with oil and gas businesses. It is believed that the expectations reflected in these statements are reasonable but they may be affected by a variety of variables and changes in underlying assumptions which could cause actual results or trends to differ materially, including but not limited to: price fluctuations, actual demand, currency fluctuations, drilling and production results, reserve estimates, loss of market, industry competition, environmental risks, physical risks, legislative, fiscal and regulatory developments, economic and financial market conditions in various countries and regions, political risks, project delay or advancement, approvals and cost estimates.

All references to dollars, cents or \$ in this presentation are to US currency, unless otherwise stated.

References to “Woodside” may be references to Woodside Petroleum Ltd. or its applicable subsidiaries.

Introduction

Developing the decommissioning scope

- 1. Decommissioning planning**
- 2. Field operational history** - Understanding field specifics and technical differences.
- 3. Subsea flushing** - Demonstrate ALARP residual Oil In Water (OIW)
- 4. Contaminated materials** (Normally Occurring Radioactive Materials)
- 5. Engineering, design and contingency plans** for all events
- 6. Equipment divestment or disposal?**

1. Decommissioning planning

- Decommissioning planning should generally start one to two years before Cessation of Production (CoP).
- Provides the opportunity to add value and prevent asset value erosion.
- Need to consider the entire decommissioning system scope at the start. Decisions made early can influence future phased costs.
- Decommissioning is the opposite of field development. It starts with the huge amount of engineering design data available which has to be reduced down to what's necessary for the scope **OR** engineering applied to resolve uncertainties or concerns to mitigate risks.

Decommissioning in practice - example



2. Operational history - Understand the field and any technical issues.


- Production and injection fluid composition changes over field life and any risks with this in the system.
- Well integrity concerns - downhole corrosion, annulus fluid, final reservoir pressures if being left unmonitored for a period of time before Plug & Abandon. Frequency of visual inspections post sail away.
- Technical integrity or process safety deviations from original design.
- System blowdown and depressurisation to ambient can provide challenging operating conditions to be managed within design envelopes.
- Potential leak paths to environment or fluid transfer i.e. via passing valves, gas lift mandrels or subsurface control line flow paths.
- Hazardous contaminants in spools, manifolds, flowlines and topsides. Topsides analysis is primary point to gather data prior to sail away.

Decommissioning in practice - example



3. Subsea flushing - Demonstrate ALARP residual OIW

- Subsea system flushing and well isolation procedures should be prepared well in advance of CoP. Timing can change quickly with critical equipment failures.
- Flushing ideally requires turbulent flow allowing reduced volumes and chemical usage. Specific to system size and pressure limits requiring engineering time to develop necessary procedures.
- Residual OIW ppm converted to a final OIW actual volume i.e. 100 ppm in 100 m³ system = 10 litres residual oil.



4. Contaminated materials

Develop management and mitigation plans for unexpected findings which may not be obvious from non intrusive topsides sampling.

Disposal options;

1. Dispose of concentrated waste after cleaning the item.
2. Dispose of the entire contaminated item.

Consider cleaning options;

1. In-situ at source with scale dissolver product (residence time?).
2. HP water jet at the onshore general disposal site to concentrate the waste.
 - Local disposal locations.
 - International disposal of concentrated waste and associated freight and regulatory approvals.



Water Injection riser with NORM's scale

5. Engineering, design and contingency plans

- Challenging engineering requirements for technically complex operations.
 - Intervening on aged equipment. Will the equipment operate?
 - Integrity concerns. Installation load conditions vs removal load conditions and installed equipment.
 - Marine growth impact to recovery loads.

- Schedule and weather requirements for operations.
 - Consider CoP timing and any immediate weather critical scope requirements.
 - Equipment heavy lifts and recovery.



Decommissioning in practice - example



6. Equipment divestment or disposal

- Subsea equipment has high capital cost.
- Negligible value for the recovered items.
- High refurbishment costs for re-use.
- Re-installation costs and residual risks of used, refurbished hardware.
- Generally old equipment – obsolescence issues.



Disposal of recovered material

Recycling of recovered product is main option.

- Adds HS exposure with handling and operations potentially being in a low labour cost environment.
- Minimal return for scrap material.

Description Of Materials	Weight (Metric Tonnes)
Riser / Umbilical Cord 8"	565.92
- Iron (70%) - Recycled	
- Plastic (20%) - Recycled	
- Duplex 2205 (5%) - Recycled	
- Fiber (2%) - Disposed	
- Wastage (3%) - Material Loss	
Riser / Umbilical Cord 6"	130.18
- Iron (70%) - Recycled	
- Plastic (20%) - Recycled	
- Copper (2%) - Recycled	
- Fiber (2%) - Disposed	
- Wastage (6%) - Material Loss	
Iron Scrap	235.19
- 100 % - Recycled	
Stainless Steel	28.50
- 100% - Recycled	

Summary

- Time for preparation of a decommissioning project should not be underestimated.
- Recovery of subsea equipment can be more challenging than installation and exposes personnel to additional risk i.e. aging equipment, unknown integrity for lifting and recovery loads.
- Develop comparison ALARP and NEBA positions for HS and E risks to consider in-situ decommissioning.
- Questions?



Typical FPSO On-station